

Patented Oct 14 1964

BE IT KNOWN that I, *Dietmar WANNKE*, have invented  
certain new and useful improvements in

***METHOD FOR SPEECH CONTROL OF AN ELECTRICAL DEVICE***

of which the following is a complete specification:

1  
 2  
 3  
 4  
 5  
 6  
 7  
 8  
 9  
 10  
 11  
 12  
 13  
 14  
 15  
 16  
 17  
 18  
 19  
 20  
 21  
 22  
 23  
 24  
 25  
 26  
 27  
 28  
 29  
 30  
 31  
 32  
 33  
 34  
 35  
 36  
 37  
 38  
 39  
 40  
 41  
 42  
 43  
 44  
 45  
 46  
 47  
 48  
 49  
 50  
 51  
 52  
 53  
 54  
 55  
 56  
 57  
 58  
 59  
 60  
 61  
 62  
 63  
 64  
 65  
 66  
 67  
 68  
 69  
 70  
 71  
 72  
 73  
 74  
 75  
 76  
 77  
 78  
 79  
 80  
 81  
 82  
 83  
 84  
 85  
 86  
 87  
 88  
 89  
 90  
 91  
 92  
 93  
 94  
 95  
 96  
 97  
 98  
 99  
 100  
 101  
 102  
 103  
 104  
 105  
 106  
 107  
 108  
 109  
 110  
 111  
 112  
 113  
 114  
 115  
 116  
 117  
 118  
 119  
 120  
 121  
 122  
 123  
 124  
 125  
 126  
 127  
 128  
 129  
 130  
 131  
 132  
 133  
 134  
 135  
 136  
 137  
 138  
 139  
 140  
 141  
 142  
 143  
 144  
 145  
 146  
 147  
 148  
 149  
 150  
 151  
 152  
 153  
 154  
 155  
 156  
 157  
 158  
 159  
 160  
 161  
 162  
 163  
 164  
 165  
 166  
 167  
 168  
 169  
 170  
 171  
 172  
 173  
 174  
 175  
 176  
 177  
 178  
 179  
 180  
 181  
 182  
 183  
 184  
 185  
 186  
 187  
 188  
 189  
 190  
 191  
 192  
 193  
 194  
 195  
 196  
 197  
 198  
 199  
 200  
 201  
 202  
 203  
 204  
 205  
 206  
 207  
 208  
 209  
 210  
 211  
 212  
 213  
 214  
 215  
 216  
 217  
 218  
 219  
 220  
 221  
 222  
 223  
 224  
 225  
 226  
 227  
 228  
 229  
 230  
 231  
 232  
 233  
 234  
 235  
 236  
 237  
 238  
 239  
 240  
 241  
 242  
 243  
 244  
 245  
 246  
 247  
 248  
 249  
 250  
 251  
 252  
 253  
 254  
 255  
 256  
 257  
 258  
 259  
 260  
 261  
 262  
 263  
 264  
 265  
 266  
 267  
 268  
 269  
 270  
 271  
 272  
 273  
 274  
 275  
 276  
 277  
 278  
 279  
 280  
 281  
 282  
 283  
 284  
 285  
 286  
 287  
 288  
 289  
 290  
 291  
 292  
 293  
 294  
 295  
 296  
 297  
 298  
 299  
 300  
 301  
 302  
 303  
 304  
 305  
 306  
 307  
 308  
 309  
 310  
 311  
 312  
 313  
 314  
 315  
 316  
 317  
 318  
 319  
 320  
 321  
 322  
 323  
 324  
 325  
 326  
 327  
 328  
 329  
 330  
 331  
 332  
 333  
 334  
 335  
 336  
 337  
 338  
 339  
 340  
 341  
 342  
 343  
 344  
 345  
 346  
 347  
 348  
 349  
 350  
 351  
 352  
 353  
 354  
 355  
 356  
 357  
 358  
 359  
 360  
 361  
 362  
 363  
 364  
 365  
 366  
 367  
 368  
 369  
 370  
 371  
 372  
 373  
 374  
 375  
 376  
 377  
 378  
 379  
 380  
 381  
 382  
 383  
 384  
 385  
 386  
 387  
 388  
 389  
 390  
 391  
 392  
 393  
 394  
 395  
 396  
 397  
 398  
 399  
 400  
 401  
 402  
 403  
 404  
 405  
 406  
 407  
 408  
 409  
 410  
 411  
 412  
 413  
 414  
 415  
 416  
 417  
 418  
 419  
 420  
 421  
 422  
 423  
 424  
 425  
 426  
 427  
 428  
 429  
 430  
 431  
 432  
 433  
 434  
 435  
 436  
 437  
 438  
 439  
 440  
 441  
 442  
 443  
 444  
 445  
 446  
 447  
 448  
 449  
 450  
 451  
 452  
 453  
 454  
 455  
 456  
 457  
 458  
 459  
 460  
 461  
 462  
 463  
 464  
 465  
 466  
 467  
 468  
 469  
 470  
 471  
 472  
 473  
 474  
 475  
 476  
 477  
 478  
 479  
 480  
 481  
 482  
 483  
 484  
 485  
 486  
 487  
 488  
 489  
 490  
 491  
 492  
 493  
 494  
 495  
 496  
 497  
 498  
 499  
 500  
 501  
 502  
 503  
 504  
 505  
 506  
 507  
 508  
 509  
 510  
 511  
 512  
 513  
 514  
 515  
 516  
 517  
 518  
 519  
 520  
 521  
 522  
 523  
 524  
 525

Electrical devices in form of vehicle navigation devices are known, in which information is to be inputted, such as for example a location name of a navigation target can be inputted by spelling. A correction within a running speech inputting is not provided. If a correction of inputting information must be performed, this can be done only after the end of the inputting procedure by repeating the speech input for the desired information. This method can be considered to be quite complicated, and can significantly distract the driver of a motor vehicle from traffic actions.

## SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to provide a method for speech controlling of an electrical device, which eliminates the disadvantages of the prior art.

The inventive method for speech control of an electrical device, in which the informations to be inputted are inputted by spelling and in which a detected character or a detected character sequence is outputted for acknowledgment of the character input, has the advantage that after the input of a character the user receives an information about the character which is actually recognized by the device or the actual recognized character sequence. This provides for a possibility of an immediate correction of the input in the case of a falsely recognized speech input. A complicated complete repeating of the speech input is therefore avoided.

By the outputting of the signs before the next input, advantageously an interactive operation with the electrical device is provided, so that the input and recognition error are excluded early and thereby the input is simplified.

In accordance with the present invention, it is preferable when an acoustic and/or optical output is provided. Thereby a simple control of the input is possible.

Furthermore, it is advantageous when for correction of a not correctly recognized character or not correctly recognized character sequence, the previously inputted characters or the previously inputted character sequence is again inputtable. For this purpose advantageously a correction command in form of a speech input is inputted, which acts for an erasing of the previously inputted characters or the previously inputted character sequence.

For acceleration of the speech input procedure it is further advantageous when in accordance with a further embodiment of the present invention, during determination of correspondence of a sequence of individual inputted characters with a stored information or at the beginning of a stored information, the stored information is inputted as an input proposal. It is especially advantageous to provide a possibility of taking over an outputted input proposal by speech input of a confirmation command at a desired input.

Furthermore, in accordance with a preferable embodiment of the invention, an input proposal by speech input of a further character or a

further character sequence is rejected. After the speech input of a further character, then advantageously the previously rejected input proposal is no longer considered as an input proposal, when the then inputted characters are contained in the rejected input proposal. Thus, the possibility is provided for generation of further, deviating input proposals, which make possible a further acceleration of the input procedure.

It is especially advantageous when the speech input for a navigation system is provided. This type of input is simple and easily learnable and a driver does not distract from traffic actions.

In particular, with the present invention, the target and/route input are significantly simplified. Also, they are performed in a reliable and fast manner.

An especially simple distinguishable feature for the electrical device is the input of individual characters for the purpose of a character sequence for a command. Thereby the electric device can engage the proper storage and find the searched answer.

The novel features which are considered as characteristic for the present invention are set forth in particular in the appended claims. The invention itself, however, both as to its construction and its method of

operation, together with additional objects and advantages thereof, will be best understood from the following description of specific embodiments when read in connection with the accompanying drawings.

FIG. 20: DETAIL

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a view showing a block diagram of a part of an electrical device which is important for the invention, for performing an inventive method; and

Figure 2 is a view showing a flow chart of a preferable embodiment of the inventive method of speech inputting.

TO BE CONTAINED

## DESCRIPTION OF THE PREFERRED EMBODIMENTS

Figure 1 shows a block diagram of an electrical device for performing a method in accordance with the present invention.

The electrical device which is to be controlled by speech inputting is provided with a microphone 12 for receiving spoken informations. The output signals of the microphone 12 are supplied to a control 10. The control 10 is formed preferably as a program-controlled microprocessor. By controlling of corresponding functions for realization of the operational course and operations of the device, operational programs can be processed in the microprocessor as components of the control.

A storage 14 is connected with the control 10. In the storage a speech data and the elements of a speech pattern associated with the speech data are stored. The speech data include in this case 26 characters of the German alphabet including three umlauts, such as Ä, Ö, and Ü, further the numerals 0 to 9, and the command words "BACK" and "INPUT". At least one speech pattern is associated in the storage 14 with each element of the speech data, namely the characters, the umlauts, the numerals and the command words. In the case of several conventional pronunciations of one element of the speech data, such as for example the number 2 which can be pronounced in German as "ZWEI" and "ZWO", all used speech patterns are



preferably associated with a corresponding elements of the speech data in the storage 14.

For comparing a speech signal received through the microphone 12 with the speech patterns stored in the storage 14, the control 10 is provided with a comparison unit 101, which preferably can be a part of the operational program of the device in form of software. The comparison unit 101 determines, from the quantity of the speech patterns stored in the storage 14, a speech pattern which has the greatest coincidence with the received signal. If the value of the determined coincidence is over an average value, the characters, umlauts, numerals or commands associated with the determined speech pattern are recognized as correct. If the value of the determined coincidence between the received speech signal and similar speech pattern is above an average value, it is decided that the received speech signal does not correspond to any of the stored speech patterns and therefore does not represent any valid input.

An output unit 16 is finally connected with the control 10 for indication and/or acoustic outputting of one or several characters, umlauts, numerals or commands received by the microphone 12. If the comparison unit 101 determines the coincidence of a speech input with a stored speech pattern, then one or several associated characters, umlauts, numerals or

commands are outputted for acknowledgment of the speech input via the output unit, or in another words indicated and/or acoustically outputted.

In accordance with a preferable embodiment of the invention, instead of a speech input up to the above mentioned command of only individual characters, additionally also a speech input of character sequences of for example two characters is provided. For this purpose the control 10 is designed so that, after a speech input of one or a first character, umlaut, or numeral, an acknowledgment of the known speech input is performed when after the speech input a predetermined time period is exceeded. If to the contrary a further speech input is performed within the predetermined time interval, than it is logically associated with the immediately preceding speech input. The speech inputs which follow directly one after the other are verified in the above described manner by comparison of the individual inputs with stored patterns. In the case of the sufficiently high coincidence of the inputs with the next coming stored pattern they are accepted as correct inputted character- or symbol sequence, when in the storage 14 such character- or symbol sequence is stored. The inputted symbol sequence or preferably a control command represented by the inputted symbol sequence, is then complete outputted as acknowledgment through the output unit 16. If for example after the speech input of the character "A" within the predetermined time interval, the further speech input of the character "R" is performed, then both characters due to

the sufficient coincidence with the corresponding stored speech patterns in the storage 14 are recognized as correct. When in the storage 14 the character sequence from the character "A" and "R" is provided as abbreviation for a control command, then through the output unit 16 the output of the control command associated with the character sequence "AR" is performed, which in this case is for example "AUTORADIO". The control of the autoradio is activated by the character sequence "AR".

The quantity of the symbols stored in the storage 14, namely characters, umlauts and numbers, as well as commands and character sequences is for example context-sensitive for the comparison operations allowed or locked. Such characters-or symbol sequences, which in connection with an actual control function represent no valid control commands, are excluded from comparison operations. For example with the character sequence "NA" a vehicle navigation device is inquired and subsequently by speech input of the character sequence "ZI" the input of a target location for the vehicle navigation device is started, for example the character sequence "NA" is excluded from the comparison operations as a character sequence which produces no valid control commands. In a similar way, for example during the target location input, such characters can be excluded from the comparison operations and thereby from the speech input, which in connection with the previously inputted characters provide no valid target location contained in a map base. The map base can be realized

preferably in form a mass storage 18 connected with the control 10, for example as a CD-ROM introduced in a CD-ROM reading device.

As a target- route inputs all desirable locations, streets, buildings etc. of a stored street map (for example CD-ROM) can be inputted by the speech input of individual characters, symbols and numerals. Control commands to the contrary are inputted basically in a symbol sequence with at least two symbols, as explained herein above. It is also provided so that for the control command complete syllables or words can be utilized, for example "INPUT".

The inventive input method is illustrated by a flow chart which is substantially represented in Figure 2.

The process starts with step 105, with turning on of the speech-control device 1.

In step 110 a speech input is performed by receiving of one or several symbols spoken by the user, for example characters, umlauts and numerals, symbol sequences or commands.

If in step 120 it is determined that during the speech input it deals with symbol contained in the storage 14, it is then indicated and/or acoustically outputted in step 125 for acknowledgment of the speech input.

In step 130, in the map storage 18, after a coincidence of an inputted character or symbol or an inputted character- or symbol sequence with an input, for example target names starting with the inputted character or the inputted character sequence are searched. If such an input is detected in step 135 it is presented and/or acoustically outputted as an input proposal by the output unit 16. In step 140 in the case of the indication of the input proposal, an input cursor which marks the next position to be inputted is displaced to the position which follows the inputted characters.

If in the following input step 110 the speech input of a confirmation command, such as the word "INPUT" is performed, and if due to comparison operations performed in step 115 it is associated with a corresponding input in the storage 14, then in step 120 it is determined that during the last speech input it does not deal with a character and subsequently in step 150 it is determined that a speech input represents a speech sequence. In step 155 this character sequence is recognized as a confirmation command "INPUT", and therefore in step 205 the offered input proposal is taken over as an input. The process ends in step 210 after the conclusion of the speech input.

If in step 110, instead of the speech input of the confirmation command, an input of correction command namely for example the instruction BACK is performed, and if in step 115 in the storage 14 a correction command is associated, then in step 120 it is determined that during the actual inputting it does not deal with a character- or symbol input. In step 150 is then determined that the actual input is a character sequence. In step 155 it is determined that the character sequence is not a confirmation command, and in step 160 it is determined that the character sequence is a correction command. Because of the input of a correction command, in step 190 the previously performed input, for example the previously inputted character is, during indication of the input the input curser is placed at the previously inputted character or symbol, and the input procedure is advanced with a new speech input in step 110.

If in step 110 a speech input is performed, which due to unclear pronunciation, external disturbance noise or the fact that this input is context sensitive excluded, has no or an unsufficient coincidence with the speech pattern stored in the storage, then in step 120 it is determined that during the actual input it deals with no valid symbol- or character sequence. In step 150 it is determined that during the actual input also no valid character- or symbol sequence takes place. The input is then ignored and the process proceeds with the further input in step 110.

If for example in step 110 a speech input of a symbol- or character sequence is performed, whose individual symbols or characters are clearly associated in step 115 with speech patterns, and which together with an abbreviation in the storage 14 correspond to a control command, then in step 120 it is determined that during the actual input it deals not with an individual character or an individual symbol. In step 150 it is determined that the valid character- or symbol sequence is provided. In steps 155 and 160 it is determined that the actual input does not correspond either to a confirmation command or a correction command. Then in step 165 the recognised character sequence is indicated as an acknowledgment and/or acoustically outputted. In step 170 the control command corresponding to the character- or symbol sequence is read and in step 175 outputted as an input offer , which is taken by producing a confirmation command in the following input step 110 or can be declined by input of a correction command in step 110.

If in a previous input step 110 a character or symbol is introduced and therefore an entry from the mass storage is outputted as an input proposal, then it is rejected by a new character- or symbol input and is marked in the mass storage as not to be considered for following comparison operations. Because of the new character input, then a new input proposal is outputted.

The inventive process is illustrated as an example for a target location input in a vehicle navigation system.

Step 105: start of the speech input

Step 110: speech input of character "S"

Step 115: comparison of the input with storage contents

Step 120: character "S" is recognized

Step 125: output of character "S"

Step 130: determination of the coincidence "SAARBRÜCKEN"

Step 135: output of the coincidence "SAARBRÜCKEN"

Step 130: input curser is further moved to a position

Step 110: speech input of character "A"

Step 115: comparison of the input with storage content

Step 120: character "A" is recognized

Step 125: output of character "A"

Step 130: determination of coincidence "SAARBURG", coincidence "SAARBRÜCKEN" is no longer considered since due to a further character input it is rejected.

Step 135: output of the coincidence "SAARBURG"

Step 140: input curser is moved further to a position.

Step 110: speech input of character "A"

Step 115: comparison of the input with storage contents





Step 130: determination of the coincidence  
"SAARHÖLZBACHG"

Step 135: output of the coincidence "SAARHÖLZBACHG"

Step 140: input curser is moved further to a position?

Step 110: speech input of character "R"

Step 115: comparison of the input with storage contents

Step 120: character "R" is interpreted because of unclear  
pronunciation because of interference noises as a character sequence "AR"

Step 150: understood input is a character sequence "AR"

Step 155: character sequence "AR" is no confirmation

Step 160: character sequence "AR" is no correction command

Step 165: understood character sequence "AR" is outputted

Step 170: determination of the coincidence "AUTORADIO"

Step 175: output of the coincidence "AUTORADIO"

Step 110: is "BACK!"

Step 115: comparison of the input with storage contents

Step 120: input with no character

Step 150: input with no character sequence

Step 155: input with no confirmation

Step 160: input is correction command

Step 190: coincidence of "AUTORADIO" is rejected. The input  
curser is replaced to the position behind the previously inputted characters.

Step 110: speech input of character "R"

Step 120: character "R" is recognized

Step 125: output of character "R"

Step 130: determination of the coincidence "SAARLOUIS"

Step 135: output of the coincidence "SAARLOUIS"

Step 140: input curser is moved further to a position

Step 110: speech input "INPUT!"

Step 115: comparison of the input with storage contents

Step 120: input with no character

Step 150: input is character sequence

Step 155: input is confirmation

Step 205: offered coincidence is taken over

Step 210: end of the speech input.

It will be understood that each of the elements described above, or two or more together, may also find a useful application in other types of methods differing from the types described above.

While the invention has been illustrated and described as embodied in method for speech control of an electrical device, it is not intended to be limited to the details shown, since various modifications and structural changes may be made without departing in any way from the spirit of the present invention.

Without further analysis, the foregoing will so fully reveal the gist of the present invention that others can, by applying current knowledge, readily adapt it for various applications without omitting features that, from the standpoint of prior art, fairly constitute essential characteristics of the generic or specific aspects of this invention.

What is claimed as new and desired to be protected by Letters Patent is set forth in the appended claims.

P. O. Box 1000, New York, N. Y. 10108